

# PRODUCT DATA SHEET

## Sikafloor® Copper tape

### COPPER FOIL ADHESIVE TAPE FOR ELECTROSTATIC CONDUCTIVE FLOORS

#### DESCRIPTION

Sikafloor® Copper tape is a self-adhesive copper tape to connect electrostatic conductive floor systems to ground

#### USES

- Conductive tape to ground decorative and protective electrostatic conductive flooring systems used in automotive, electronics and pharmaceutical manufacturing, storage facilities and warehouses.

#### CHARACTERISTICS / ADVANTAGES

- Electrostatically conductive
- Self-adhesive
- Economical

#### PRODUCT INFORMATION

<b>Packaging</b>	20 m rolls. Net weight 0,080 kg/roll. Refer to current price list for packaging variations	
<b>Shelf life</b>	12 months from date of production	
<b>Storage conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.	
<b>Dimensions</b>	Width	9,0 mm
	Length	20 m
<b>Thickness</b>	~0,08–0,10 mm.	

#### APPLICATION INSTRUCTIONS

##### SUBSTRATE QUALITY / PRE-TREATMENT

Refer to the appropriate flooring system primer Product Data Sheet.

##### APPLICATION

Bond the self-adhesive copper tape onto the cured system primer and extend to the equipotential bonding point.

The copper tape connections must be carried out and approved by an electrical engineer and in accordance with any relevant local regulations.

#### BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w)

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Services AG

Tüffenwies 16

8048 Zürich

Tel: +41 58 436 4040

[www.sika.com](http://www.sika.com)



SikafloorCoppertape-en-(01-2019)-1.pdf

### PRODUCT DATA SHEET

Sikafloor® Copper tape

January 2019, Version 01.0

020816140040000001